

Model: NW-IBC15

5MP IP IR Bullet / PoE/ 20 Meters/ 4 MM Color Camera



Features

- All time color Camera
- Max Up to 5MP 2592x1904@20fps
- Compression: H.265/H.264
- Min. illumination Color: 0Lux (Warm light on)
- WDR: Support DWDR
- IR Range: 20m
- Support 3D DNR and Digital WDR
- Power Input: POE 48 V Standard / DC 12V
- POE, IP66

Camera	
Image Sensor	1/2.7" Low Illumination CMOS Sensor
Signal System	PAL/NTSC
Min. Illumination	Color: 0Lux (Warm light on)
Shutter Time	1s to 1/100,000s
Day & Night	IR Cut Filter with Auto Switch
Wide Dynamic Range	DWDR
Angle Adjustment	Bracket, pan 0~360°, tilt 0~75°, rotate 0~360°
Lens	
Lens Type	Fixed
Focus	4mm
Lens Mount	M12
Aperture	F1.6, Fixed
FOV	Horizontal field of view: 80° (4mm)
Illuminator	

IR LEDs	2 Array LED
IR Range	Up to 20m
S/N Ratio	≥50db(AGC Closed)
White LEDs/ Warm light	Yes
Compression Standard	
Video Compression	H.265/H.264
Video Bit Rate	16Kbps~3Mbps adjustable Support CBR/VBR
Audio Compression	G.711u / 64Kbps
Audio Bit Rate	8K~48Kbps
Image	
Max. Resolution	5MP 2592X1904
Main Stream	PAL: 20fps (2592x1904, 2304x 1296, 1920x 1080, 1280x 720)
	NTSC: 20fps (2592x1904,2304x 1296, 1920x 1080, 1280x 720)
Sub Stream	PAL: 25fps (704 576, 704 288, 640 360, 352 288)
	NTSC: 30fps (704 480, 704 240, 640 360, 352 240)
Image Setting	Saturation, brightness, contrast, sharpness, Chroma
Image Enhancement	BLC/3D DNR/HLC
ROI	N/A
OSD	Adaptable size, Letters Such as Week, Date, Time.
Privace Mask	Yes, 4 Zone Selectable
Mirror Flip	Off/horizontal mirroring/vertical mirroring/180° rotation
Feature	
Alarm Trigger	NA
Video Analytics	NA
Network	
Communication Interface	Rj4 10/100 mbps
Protocols	TCP/IP, HTTP, FTP, DHCP, DNS, DDNS, MULTICAST, IPV4, NTP, UDP, Telnet
System Compatibility	ONVIF
Remote Connection	Support 3 User Max
Client	Yes
Web Version	Web5
Interface	
Communication Interface	1 RJ45 10M/ 100M self adaptive Ethernet port
Audio I/O	NA
Reset Button	NA

On-board storage	
General	
Web Client	Yes
Language	English
Operating Conditions	-40 ~ 60 , 0 ~ 95% RH
Power Supply	DC 12V±25%, PoE (802.3af)
Power Consumption	≥5W
Protection	IP66
Dimensions	H90xW104x104
Weight	Weight Net: 0.182Kg Weight Gross:0.248Kg

Note: Product specification and design are subject to change without any prior notice.