

## Model: NW-IDN15

5MP IP IR Dome/ PoE/ 20 Meters/ 4 MM



### Features

- Up to 2592X1904@20fps
- Compression: H.265/H.264
- Min. illumination Color: 0.05Lux,B/W:0.01,0 Lux with IR
- WDR: Support DWDR
- IR Range: 20m
- Support 3D DNR and Digital WDR
- Power Input: POE 48 V Standard / DC 12V
- Operating Conditions -40°~60°, 0~95% RH
- POE, IP66

<b>Camera</b>	
<b>Image Sensor</b>	1/2.7" ,5MP progressive CMOS
<b>Signal System</b>	PAL/NTSC
<b>Min. Illumination</b>	Color : 0.01Lux@F1.2 ; B&W:0Lux@F1.2(IR on)
<b>Shutter Time</b>	1s to 1/100,000s
<b>Day &amp; Night</b>	IR Cut Filter with Auto Switch
<b>Wide Dynamic Range</b>	DWDR
<b>Angle Adjustment</b>	Bracket, pan 0~360°, tilt 0~75°, rotate 0~360°
<b>Lens</b>	
<b>Lens Type</b>	Fixed
<b>Focus</b>	4mm
<b>Lens Mount</b>	M12
<b>Aperture</b>	F1.6, Fixed
<b>FOV</b>	Horizontal field of view: 80° (4mm)
<b>Illuminator</b>	
<b>IR LEDs</b>	3 Array LED
<b>IR Range</b>	Up to 20m
<b>S/N Ratio</b>	≥50db(AGC Closed)

White LEDs / Warm lights	N/A
<b>Compression Standard</b>	
Video Compression	H.265/H.264
Video Bit Rate	16Kbps~4Mbps adjustable Support CBR/VBR
Audio Compression	NA
Audio Bit Rate	
<b>Image</b>	
Max. Resolution	2560x1440
Main Stream	PAL: 20fps (2592x1904, 2560x 1440, 2304x 1296, 1920x 1080, 1280x 720)
	NTSC: 25fps (2592x1904,2560x 1440), 30fps (2304 1296, 1920x 1080, 1280x 720)
Sub Stream	PAL: 25fps (704 576, 704 288, 640 360, 352 288)
	NTSC: 30fps (704 480, 704 240, 640 360, 352 240)
Image Setting	Saturation, brightness, contrast, sharpness, chroma
Image Enhancement	BLC/3D DNR/HLC
ROI	N/A
OSD	16 16, 32 32, 48 48, 64 64, adaptable size, Letters Such as Week, Date, Time, Total 3 Regions
Privace Mask	Yes, 4 Zone Selectable
Mirror Flip	Off/horizontal mirroring/vertical mirroring/180° rotation
<b>Feature</b>	
Alarm Trigger	Motion Detection, Mask Alarm, IP Address Conflict
Video Analytics	NA
<b>Network</b>	
Communication Interface	Rj4 10/100 mbps
Protocols	TCP/IP, HTTP, FTP, DHCP, DNS, DDNS, MULTICAST, IPV4, NTP, UDP, Telnet
System Compatibility	ONVIF
Remote Connection	Support 3 User Max
Client	Yes
Web Version	Web5
<b>Interface</b>	
Communication Interface	1 RJ45 10M/ 100M self adaptive Ethernet port
Audio I/O	NA
Reset Button	NA
On-board storage	
<b>General</b>	
Language	English
Operating Conditions	-40 ~ 60 , 0 ~ 95% RH
Power Supply	DC 12V±25%, PoE (802.3af)
Power Consumption	≥5W

<b>Protection</b>	IP66
<b>Dimensions</b>	110(W)*90(H)
<b>Weight</b>	Weight Net: 0.250Kg Weight Gross:0.259Kg

Note: Product specification and design are subject to change without any prior notice.