

# Model: NW-IN10232

H.265+ 32 CH 2HDD NVR



## Features

### HD Input

- 32 Ch NVR support
- Connectable to the third-party network cameras
- H.265+/H.265/H.264 video formats
- Supports live view, storage, and playback of the connected camera at up to 5MP resolution

### HD Output

- HDMI and VGA simultaneous output
- HDMI/VGA Video output at up to 2K (1080P) resolution

### HD Storage

- 2 SATA interfaces, up to 6TB for each HDD
- H.265+ compression effectively reduces the storage space and costs.

### HD Transmission

- 1xRJ45 self-adaptive 10/100/1000 Mbps network Interface

Video/Audio Input	
Video Input	32ch
Audio Input	1-ch, 3.5mm
Network	
Bandwidth	150Mbps
Mobile Software	P2P/IP for IOS & Android
Internet Protocol	TCP/UDP/HTTP/MULTICAST/UPnP/DHCP/DDNS/NTP/RTSP/SADP Etc
Email	NA
ANR	NA
Remote Connection	64
Browser	Support all browsers, including IE, Safari, Chrome, Edge. (H.265 only supports configuration in non-IE kernel browsers)
Advanced	Remaining Bandwidth Display

Video/Audio Output	
<b>HDMI Output</b>	1 channel, HDMI interface; Resolution: 2K/30Hz
<b>VGA Output</b>	1 channel, VGA interface; resolution: 1920x1080P
<b>Audio Output</b>	1-ch, RCA (Linear, 1kΩ)
<b>Recording Resolution</b>	5MP/4MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
<b>Synchronous Playback</b>	32CH x 3M Recording ; 4 CH Playback 32CH x 5M Recording ; 2 CH Playback
<b>Display Split</b>	1/4/9
Decoding	
<b>Compression</b>	H.265+/H.265/H.264
<b>Preview Capability</b>	1-ch 5MP 4-ch 3MP /32-ch 720P
<b>E-Zoom</b>	Y
Hard Disk	
<b>SATA</b>	2 SATA
<b>Capacity</b>	Up to 6 TB Capacity for Each HDD (0~45°C)
<b>NTFS Files System</b>	NA
<b>HDD Management</b>	NA
RAID	
<b>RAID Mode</b>	N/A
<b>RAID Management</b>	N/A
External Interface	
<b>HDMI Output</b>	1ch
<b>VGA Output</b>	1ch
<b>Network Interface</b>	1 RJ-45 10/100/1000 Self-adaptive Ethernet Interfaces
<b>USB Interface</b>	2 x USB2.0
<b>Alarm In/Out</b>	NA
Advance	
<b>Video Analytics(VCA)</b>	NA
<b>I-Frame Record</b>	Y
<b>Plug and Play</b>	N/A
<b>Image Flip</b>	NA
<b>Corridor Mode</b>	NA
<b>Search Mode</b>	Time/Date, Alarm, MD &Exact Search (accurate & Second), Smart Search

<b>Trigger Recording</b>	Recording, PTZ,Tour,Alarm, Video Push,Email,Buzzer, Snapshot
<b>Smart Recording</b>	Set Recording Bit Rate for Different Time
<b>Alarm Recording</b>	Pre Alarm Default 10s ( 5/10/15/60s Optional) , Post Alarm Default 10s (10/15/30/60/600s Optional ).
<b>One Key Control</b>	Intercom ,Recording, one key add
<b>Records Format</b>	SDV, MP4
<b>Records Encryption</b>	Y
<b>Records Tag</b>	Y
<b>Onvif</b>	Onvif
<b>General</b>	
<b>Language</b>	English
<b>Power Supply</b>	DC12V 2A
<b>Consumption(without HDD)</b>	≤ 15W
<b>Working Temperature</b>	-10 °C ~ +55 °C (+14 °F~ + 131 °F)
<b>Working Humidity</b>	10 % ~ 90 %
<b>Chassis</b>	1U
<b>Dimensions</b>	50mm×250mm×300mm
<b>Weight</b>	1.076(without HDD) Weight Gross 2.0KG (without HDD)

Product specification and design are subject to change without any prior notice.