

Model: NW-REMOTE CARE

3MP WIFI Pan-Tilt Remote Care Camera



Features

- PAN/TILT Remote Care Camera
- Resolution Up to 2304x1296@20fps
- Compression: H.265/H.264
- Min. illumination Color: 0.01 Lux, BW: 0.001 Lux
- WDR: Support DWDR
- IR Range: Upto 10m
- Support 3D DNR and Digital WDR
- Power Input: DC 12V-1A
- Operating Conditions -40°~60°, 0~95% RH
- Two way Audio Built-in-Mic/Speaker
- IP66

Camera	
Image Sensor	1/3" CMOS Sensor
Signal System	PAL/NTSC
Min. Illumination	Color : 0.01 Lux, BW: 0.001 Lux
Shutter Time	1s to 1/100,000s
Day & Night	IR Cut Filter with Auto Switch
Wide Dynamic Range	DWDR
Angle Adjustment	Bracket, pan 0~360°, tilt 0~75°, rotate 0~360°
Lens	
Lens Type	Fixed
Focus	3.6mm
Lens Mount	M12
Aperture	F1.6, Fixed
FOV	Horizontal field of view: 80° (4mm)

Illuminator	
IR LEDs	6 IR LED
IR Range	Up to 10m
S/N Ratio	≥39.1db
White LEDs/Warm lights	Yes
Compression Standard	
Video Compression	H.265+/H.265/H.264
Video Bit Rate	16Kbps~4Mbps adjustable Support CBR/VBR
Audio Compression	AAC/G711A
Audio Bit Rate	8K~48Kbps
Image	
Max. Resolution	2304X1296@15fps
Main Stream	PAL: 25fps (2304× 1296, 1920× 1080, 1280× 720)
	NTSC: 30fps (2304 1296, 1920× 1080, 1280× 720)
Sub Stream	PAL: 25fps (704 576, 704 288, 640 360, 352 288)
	NTSC: 30fps (704 480, 704 240, 640 360, 352 240)
Image Setting	Saturation, brightness, contrast, sharpness, chroma
Image Enhancement	BLC/3D DNR/HLC
ROI	N/A
OSD	16 16, 32 32, 48 48, 64 64, adaptable size, Letters Such as Week, Date, Time, Total 3 Regions
PTZ	Pan 0 ° -350 ° Tilt 0 ° -90 ° Horizontal speed 20 ° / S Vertical speed 10 ° / S
Mirror Flip	Off/horizontal mirroring/vertical mirroring/180° rotation
Feature	
Alarm Trigger	Motion Detection, Mask Alarm, Human Detection based Motion
Video Analytics	Intelligent motion tracking, automatically tracking when people break area
Network	
Communication Interface	
Protocols	TCP/IP, HTTP, FTP, DHCP, DNS, DDNS, MULTICAST, IPV4, NTP, UDP, Telnet
System Compatibility	N1 Protocol
Remote Connection	Support 3 User Max
Client	Yes
Web Version	
Interface	
Communication Interface	WIFI(IEEE802.11b/g/n)
Audio I/O	Supports two-way audio, built-in microphone and speaker
Reset Button	Yes
On-board storage	Yes Up to 128GB

General	
Web Client Language	16 languages English, Russian, Spanish, Korean, Italian, Turkish, Simple Chinese, Traditional Chinese, Thai, French, Polish, Dutch, Hebraism, Farsi, Arabic, Vietnamese
Operating Conditions	-0 ~ 50, 0 ~ 95% RH
Power Supply	DC 5V 1A
Power Consumption	≤3W
Protection	IP66, Lightning protection, surge protection and voltage transient protection meets
Dimensions	W71XH162XL204 Plastic
Weight	Weight Net: 0.187Kg Weight Gross:0.319Kg

Note: Product specification and design are subject to change without any prior notice.