

Model: NWS004

10/100 Mbps 4+2 Port 250m PoE Switch
With built-in Power Supply

Features

- 4*10/100Mbps PoE ports, 2*10/100Mbps uplink port
- Support IEEE802.3af/at
- Support Max Transmission distance up to 250m with PoE Power
- Built-in power supply
- Maximum power of single PoE port: 30W
- Maximum PoE power: 78W
- Support lightning protection 2000V
- Power circuit protection

Specification	Description
Network Port	4 10/100Mbps PoE RJ45 port (Port 1~ Port4)
	2 10/100Mbps RJ45 port uplink(Port5~Port 6)
Transmission Distance	1 ~ 4 PoE Port : 100Mbps: 0~100 Meter ;
	1 ~ 4 PoE Port : 10Mbps: 0~250 Meter
Transmission Medium	Cat5/5e/6 standard network cable
Network Standard	IEEE802.3/802.3u, IEEE802.3x,IEEE802.ab
Performance	Switching Capacity : 1.2Gbps (no block)
	Packet Buffer Memory : 1Mbits
	Throughput : 0.9Mbps, MAC Table: 1K
	Packet Forwarding rate : 10Mbps: 14880pps/port 100Mbps: 148800pps/port
Power Over Ethernet	PoE Standard: IEEE 802.3af/at
	PoE Power Supply: End-Span(1/2+;3/6-)
	PoE Power: af=15.4W,at=30W for each port
RJ 45 Port	Port Function: Power priority mechanism, fast and forward,
	MAC automatic learning and aging IEEE802.

	3X Full-duplex mode and backpressure for Half-duplex mode
LED Indicator	LINK/ACT.100Mbps;PoE Status Indicator; Power indicator; Extender
Environment	Operating Temperature : 0°~55°C
	Storage Temperature : -20°C~70°C
	Operating Humidity : 20%~ 95%, Non-condensing
Dimensions	Size(LxWxH) : 202mm*140mm*45mm
	Weight : 0.95kg

Note: Product housing specifications are subject to change without prior notice. .